

NOTES:

1. ALL DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5M-1994.
2. DATUM PLANE H LOCATED AT MOLD PARTING LINE AND COINCIDENT WITH LEAD, WHERE LEAD EXITS PLASTIC BODY AT BOTTOM OF PARTING LINE.
3. DATUMS A-B AND D TO BE DETERMINED AT CENTERLINE BETWEEN LEADS WHERE LEADS EXIT PLASTIC BODY AT DATUM PLANE H.
4. LEADS TO BE DETERMINED AT SEATING PLANE C.
5. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD PROTRUSION, ALLOWABLE MOLD PROTRUSION IS 0.254 MM ON D1 AND E1 DIMENSIONS.
6. 'N' IS THE TOTAL NUMBER OF TERMINALS.
7. THESE DIMENSIONS TO BE DETERMINED AT DATUM PLANE H.
8. PACKAGE TOP DIMENSIONS ARE SMALLER THAN BOTTOM DIMENSIONS AND TOP OF PACKAGE WILL NOT OVERHANG BOTTOM OF PACKAGE.
9. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION, ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08mm TOTAL IN EXCESS OF THE b DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT.
10. CONTROLLING DIMENSION: MILLIMETER.
11. MAXIMUM ALLOWABLE DIE THICKNESS TO BE ASSEMBLED IN THIS PACKAGE FAMILY IS 0.38 MILLIMETERS.
12. THIS OUTLINE CONFORMS TO JEDEC PUBLICATION 95 REGISTRATION MS-026, VARIATIONS BHA & BHB, A1 IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT OF THE PACKAGE BODY.

**JEDEC VARIATION
ALL DIMENSIONS IN MILLIMETERS**

SYMBOL	BHA			N D T E	BHB			N D T E
	MIN.	NDM.	MAX.		MIN.	NDM.	MAX.	
A	0.05	0.30	1.60	13	0.05	0.20	1.60	13
A1	1.35	1.40	1.45	4	1.35	1.40	1.45	4
A2								
D		22.00 BSC.		4		22.00 BSC.		4
D1		20.00 BSC.		7,8		20.00 BSC.		7,8
E		16.00 BSC.		4		16.00 BSC.		4
E1		14.00 BSC.		7,8		14.00 BSC.		7,8
L	0.45	0.60	0.75		0.45	0.60	0.75	
N		100				128		
e		0.65 BSC				0.50 BSC.		
b	0.22	0.32	0.38	9	0.17	0.22	0.27	9
b1	0.22	0.30	0.33		0.17	0.20	0.23	
ccc	0.10	0.10	0.10		0.08	0.08	0.08	
ddd	0.13	0.13	0.13		0.08	0.08	0.08	

TITLE	PACKAGE OUTLINE, LQFP, 14 X 20 MM BODY,
SIZE	100V/0.10 MM FURRY, 140 MM THICK
REV.	34512
REV.	08
FORM	6/1
SHEET	2 OF 2