

**NOTES:**

- 1. ALL DIMENSIONING AND TOLERANCING CONFORM TO ANSI Y14.5M-1994.
- 2. DATUM PLANE [ ] LOCATED AT MOLD PARTING LINE AND COINCIDENT WITH LEAD WHERE LEAD EXITS PLASTIC BODY AT BOTTOM OF PARTING LINE.
- 3. DATUM [ ] AND [ ] TO BE DETERMINED AT CENTERLINE BETWEEN LEADS WHERE LEADS EXIT PLASTIC BODY AT DATUM PLANE [ ] .
- 4. TO BE DETERMINED AT SEATING PLANE [ ] .
- 5. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE MOLD PROTRUSION IS 0.294 MM ON D1 AND E1.
- 6. DIMENSIONS TOTAL NUMBER OF TERMINALS.
- 7. THESE DIMENSIONS TO BE DETERMINED AT DATUM PLANE [ ] .
- 8. PACKAGE TOP DIMENSIONS ARE SMALLER THAN BOTTOM DIMENSIONS AND TOP OF PACKAGE WILL NOT OVERHANG BOTTOM OF PACKAGE.

- 9. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08mm TOTAL. ALL DIMENSIONS SHALL BE TAKEN IN THE UNSTRESSED CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT.
- 10. CONTROLLING DIMENSION: MILLIMETER.
- 11. MAXIMUM ALLOWABLE DIE THICKNESS TO BE ASSEMBLED IN THIS PACKAGE FAMILY IS 0.38 MILLIMETERS.
- 12. THIS OUTLINE CONFORMS TO JEDEC PUBLICATION 95 REGISTRATION MS-026, VARIATION BGA & BGB.
- 13. A1 IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT OF THE PACKAGE BODY.
- 14. DIMENSION D2 AND E2 REPRESENT THE SIZE OF THE EXPOSED PAD. THE ACTUAL DIMENSIONS ARE SPECIFIED ON THE BONDING DIAGRAM, AND IS DEPENDENT ON THE DIE SIZE.
- 15. EXPOSED PAD SHALL BE COPLANAR WITH BOTTOM OF PACKAGE WITHIN 0.05. CORNER CHAMFER OF EXPOSED DIE PAD SHALL BE WITHIN 0.30 MM.

JEDEC VARIATION ALL DIMENSIONS IN MILLIMETERS				
SYMBOL	BGA			N T E
	MIN.	NDM.	MAX.	
A	~	~	1.60	13
A1	0.05	~	0.15	
A2	1.35	1.40	1.45	4
D	26.00 BSC.			
D1	24.00 BSC.			7.8
E	26.00 BSC.			4
E1	24.00 BSC.			7.8
L	0.45	0.60	0.75	9
N	*160, 176			
e	0.50 BSC.			9
b	0.17	0.22	0.27	
b1	0.17	0.20	0.23	9
ccc	~	~	0.08	
ddd	~	~	0.08	

\* NOTE: THE 160 LEAD IS A COMPLIANT DEREGULATION OF THE 176 LEAD MS-026 VARIATION BGA.

JEDEC VARIATION ALL DIMENSIONS IN MILLIMETERS				
SYMBOL	BGB			N T E
	MIN.	NDM.	MAX.	
A	~	~	1.60	13
A1	0.05	~	0.15	
A2	1.35	1.40	1.45	4
D	26.00 BSC.			
D1	24.00 BSC.			7.8
E	26.00 BSC.			4
E1	24.00 BSC.			7.8
L	0.45	0.60	0.75	9
N	216			
e	0.40 BSC.			9
b	0.13	0.18	0.23	
b1	0.13	0.16	0.19	9
ccc	~	~	0.08	
ddd	~	~	0.07	

THE DIMENSIONS AND TOLERANCING SPECIFIED HEREIN ARE THE PROPERTY OF ANIRKOR TECHNOLOGY. NO PART OF THIS DOCUMENT IS TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT PERMISSION IN WRITING FROM ANIRKOR TECHNOLOGY.


REVISION IS AN ACTUAL SIZE  
FORM NO. 000-000-0000

SEE PAGE 1

32780

14

2 of 2



**Ankor**  
Technology

www.ankor.com

PACKAGE OUTLINE: MATRIX LQFP,  
24 X 24 mm BODY, 1.00/0.10 mm FORM,  
1.40 mm THICK (OPTIONAL PAD)