

NOTES:

1. DIE THICKNESS ALLOWABLE IS 0.305mm MAXIMUM(.012 INCHES MAXIMUM)
2. DIMENSIONING & TOLERANCES CONFORM TO ASME Y14.5M. – 1994.
3. N IS THE NUMBER OF TERMINALS.  
Nd IS THE NUMBER OF TERMINALS IN X-DIRECTION &  
Ne IS THE NUMBER OF TERMINALS IN Y-DIRECTION.
4. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30mm FROM TERMINAL TIP.
5. THE PIN #1 IDENTIFIER MUST BE EXISTED ON THE TOP SURFACE OF THE PACKAGE BY USING INDENTATION MARK OR OTHER FEATURE OF PACKAGE BODY.
6. EXACT SHAPE AND SIZE OF THIS FEATURE IS OPTIONAL.
7. ALL DIMENSIONS ARE IN MILLIMETERS.
8. THE SHAPE SHOWN ON FOUR CORNERS ARE NOT ACTUAL I/O.
9. BILATERAL COPLANARITY ZONE APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.
10. APPLIED ONLY FOR TERMINALS.
11. Q AND R APPLIES ONLY FOR STRAGHT TIEBAR SHAPES.
12. FOR 0.40mm LEAD PITCH, THE LEAD POSITION TOLERANCE MUST BE 0.07mm AT THE ACTUAL MEAN VALUE OF BODY SIZE.



www.amkor.com

PACKAGE OUTLINE, MIF2, 7 X 7 mm BODY

SIZE	NO. TERMINALS	DATE NUMBER	SCALE	NO. OF SHEETS
A3	N/A		45277	13
PRINTING IS AN ACTUAL SCALE	FORM NO. MIF_2_7X7	NO. SHEET NO.	001-0000-3917	3 of 3

THE DRAWING AND INFORMATION CONTAINED HEREIN ARE THE SOLE PROPERTY OF AMKOR TECHNOLOGY. AMKOR TECHNOLOGY AND DESIGN ENGINEERS ASSUME NO LIABILITY FOR ANY DAMAGE TO THE PROPERTY OF ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AMKOR.