

NOTES:

1. DIE THICKNESS ALLOWABLE IS 0.305mm MAXIMUM(.012 INCHES MAXIMUM)
2. DIMENSIONING & TOLERANCES CONFORM TO ASME Y14.5M. – 1994.
3. N IS THE NUMBER OF TERMINALS.  
Nd IS THE NUMBER OF TERMINALS IN X-DIRECTION &  
Ne IS THE NUMBER OF TERMINALS IN Y-DIRECTION.
4. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.20 AND 0.25mm FROM TERMINAL TIP.
5. THE PIN #1 IDENTIFIER MUST BE EXISTED ON THE TOP SURFACE OF THE PACKAGE BY USING INDENTATION MARK OR OTHER FEATURE OF PACKAGE BODY.
6. EXACT SHAPE AND SIZE OF THIS FEATURE IS OPTIONAL.
7. ALL DIMENSIONS ARE IN MILLIMETERS.
8. PACKAGE WARPAGE MAX 0.08mm.
9. APPLIED FOR EXPOSED PAD AND TERMINALS.  
EXCLUDE EMBEDDING PART OF EXPOSED PAD FROM MEASURING.
10. APPLIED ONLY FOR TERMINALS.

SYMBOL	PITCH VARIATION			NOTES
	MIN.	NOM.	MAX.	
Ⓜ	0.40 BSC			
N	88			3
Nd	22			3
Ne	22			3
L	0.30	0.40	0.50	
b	0.15	0.20	0.25	4
D2	7.95	8.10	8.25	
E2	7.95	8.10	8.25	

SYMBOL	COMMON DIMENSIONS			NOTES
	MIN.	NOM.	MAX.	
A	–	0.85	0.90	
A1	0.00	0.01	0.05	10
A2	–	0.65	0.70	
A3	0.20 REF.			
D	10.00 BSC			
D1	9.75 BSC			
E	10.00 BSC			
E1	9.75 BSC			
θ			12°	
P	0.24	0.42	0.60	



PACKAGE OUTLINE, MLF2, 88 LEAD,  
10 X 10 mm BODY, 0.40 mm LEAD PITCH

DATE	REV	BY	CHKD	APP'D	DATE
	A3	101330880			305065
FORM NO.	REV	DATE	ISSUE	NO.	
306448/00	00	1001-0000-3817	12.51	2	00

PRINTING IS AN ACTUAL SCALE

THE DIMENSIONS AND INFORMATION CONTAINED HEREIN ARE THE EXCLUSIVE PROPERTY OF AMKOR. THE INFORMATION CONTAINED HEREIN IS UNCLASSIFIED/PROPRIETARY AND IS NOT TO BE RELEASED TO ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AMKOR.