

NOTES:

1. DIE THICKNESS ALLOWABLE IS 0.305mm MAXIMUM(.012 INCHES MAXIMUM)
2. DIMENSIONING & TOLERANCES CONFORM TO ASME Y14.5M. – 1994.
3. N IS THE NUMBER OF TERMINALS.
Nd IS THE NUMBER OF TERMINALS IN X-DIRECTION &
Ne IS THE NUMBER OF TERMINALS IN Y-DIRECTION.
4. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.25mm FROM TERMINAL TIP.
5. ALL DIMENSIONS ARE IN MILLIMETERS.
6. PACKAGE WARPAGE MAX 0.05mm.
7. APPLIED FOR EXPOSED PAD AND TERMINALS.
EXCLUDE EMBEDDING PART OF EXPOSED PAD FROM MEASURING.
8. APPLIED ONLY FOR TERMINALS.

S Y M B O L	COMMON DIMENSIONS			N _O T _E
	MIN.	NOM.	MAX.	
A	0.45	0.55	0.65	
d	0.25	0.30	0.35	
k	0.20	–	–	
L1	0.05	0.10	0.15	
D		10.00 BSC		
E		10.00 BSC		

S _Y M _B O _L	PITCH VARIATION			N _O T _E
	MIN.	NOM.	MAX.	
e		0.50 BSC		
N		200		3
NEd		14		3
NEb		15		3
NEC		18		3
L	0.20	0.30	0.40	
b	0.15	0.20	0.25	4
D1	5.75	5.80	5.85	
E1	5.75	5.80	5.85	