


REV	DESCRIPTION	DATE	DESIGNED BY
00	INITIAL RELEASE PER DCMG OUTLIS	10/17/90	T.M.K.
01	INCORPORATED PER DCMG A1855	04/16/97	T.M.K.
02	ADDED 100 BALL CORN, DCMG OUTLIS	07/02/97	T.M.K.
			D.S.A.

THE MANHOLE AND ASSOCIATED COMPONENTS HEREIN ARE THE PROPERTY OF AMKOR/AMK. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.



8. **INSTALLATION SPECIFICATIONS:**
- A. LAY OUT THE MANHOLE AND ASSOCIATED COMPONENTS IN ACCORDANCE WITH THE FOLLOWING DIMENSIONS:
 - B. LAY OUT THE MANHOLE AND ASSOCIATED COMPONENTS IN ACCORDANCE WITH THE FOLLOWING DIMENSIONS:
 - C. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - D. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - E. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - F. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - G. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - H. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - I. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - J. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - K. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - L. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - M. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - N. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - O. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - P. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - Q. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - R. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - S. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - T. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - U. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - V. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - W. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - X. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - Y. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
 - Z. VARIATION MAX -1 INCH FOR ALL AND 5 DIMENSIONS.
9. **MANHOLE AND ASSOCIATED COMPONENTS:**
- A. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - B. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - C. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - D. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - E. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - F. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - G. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - H. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - I. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - J. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - K. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - L. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - M. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - N. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - O. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - P. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - Q. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - R. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - S. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - T. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - U. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - V. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - W. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - X. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - Y. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
 - Z. THE MANHOLE SHALL BE USED TO PROTECT THE UNDERGROUND UTILITY FROM THE SURFACE OF THE GROUND.
10. **NOTES:**
- A. ALL DIMENSIONS AND TOLERANCES COMPARE TO ANSI Y14.5M-1994.
 - B. UNLESS OTHERWISE SPECIFIED.

TITLE: MANHOLE AND ASSOCIATED COMPONENTS		DATE: 10/17/90		DESIGNED BY: T.M.K.	
SUBTITLE: MANHOLE AND ASSOCIATED COMPONENTS		DATE: 10/17/90		DESIGNED BY: T.M.K.	
REVISIONS:		DATE: 10/17/90		DESIGNED BY: T.M.K.	
1	INITIAL RELEASE PER DCMG OUTLIS	10/17/90	T.M.K.	2	INCORPORATED PER DCMG A1855
2	ADDED 100 BALL CORN, DCMG OUTLIS	07/02/97	T.M.K.	3	
3				4	
4				5	
5				6	
6				7	
7				8	
8				9	
9				10	
10				11	
11				12	
12				13	
13				14	
14				15	
15				16	
16				17	
17				18	
18				19	
19				20	
20				21	
21				22	
22				23	
23				24	
24				25	
25				26	
26				27	
27				28	
28				29	
29				30	
30				31	
31				32	
32				33	
33				34	
34				35	
35				36	
36				37	
37				38	
38				39	
39				40	
40				41	
41				42	
42				43	
43				44	
44				45	
45				46	
46				47	
47				48	
48				49	
49				50	
50				51	
51				52	
52				53	
53				54	
54				55	
55				56	
56				57	
57				58	
58				59	
59				60	
60				61	
61				62	
62				63	
63				64	
64				65	
65				66	
66				67	
67				68	
68				69	
69				70	
70				71	
71				72	
72				73	
73				74	
74				75	
75				76	
76				77	
77				78	
78				79	
79				80	
80				81	
81				82	
82				83	
83				84	
84				85	
85				86	
86				87	
87				88	
88				89	
89				90	
90				91	
91				92	
92				93	
93				94	
94				95	
95				96	
96				97	
97				98	
98				99	
99				100	