NOTES:

1. ALL DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5M-1994.
2. DATUM PLANE H LOCATED AT MOLD PARTING LINE AND COINCIDENT WITH LEAD, WHERE LEAD EXITS PLASTIC BODY AT BOTTOM OF PARTING LINE.
3. DATUMS A-B AND D TO BE DETERMINED AT CENTERLINE BETWEEN LEADS WHERE LEADS EXIT PLASTIC BODY AT DATUM PLANE H.
4. TO BE DETERMINED AT SEATING PLANE C.
5. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE MOLD PROTRUSION IS 0.254 MM ON D1 AND E1 DIMENSIONS.
6. "N" IS THE TOTAL NUMBER OF TERMINALS.
7. THESE DIMENSIONS TO BE DETERMINED AT DATUM PLANE H.
8. PACKAGE TOP DIMENSIONS ARE SMALLER THAN BOTTOM DIMENSIONS AND TOP OF PACKAGE WILL NOT OVERHANG BOTTOM OF PACKAGE.
9. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08mm TOTAL IN EXCESS OF THE b DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT.
10. CONTROLLING DIMENSION: MILLIMETER.
11. MAXIMUM ALLOWABLE DIE THICKNESS TO BE ASSEMBLED IN THIS PACKAGE FAMILY IS 0.30 MILLIMETERS.
12. THIS OUTLINE CONFORMS TO JEDEC PUBLICATION 95 REGISTRATION MS-026, VARIATION AAA AND AAB.
13. A1 IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT OF THE PACKAGE BODY.
14. DIMENSION D2 AND E2 REPRESENT THE SIZE OF THE EXPOSED PAD. THE ACTUAL DIMENSIONS ARE SPECIFIED ON THE BONDING DIAGRAM, AND IS DEPENDENT ON THE DIE SIZE.
15. EXPOSED PAD SHALL BE COPLANAR WITH BOTTOM OF PACKAGE WITHIN 0.05.
16. CORNER CHAMFER OF EXPOSED DIE PAD SHALL BE WITHIN 0.30 MM.

SYMBOL	ALL DIMENSIONS IN MILLIMETERS			NOTE
	MIN.	NOM.	MAX.	
A	---	---	1.20	
A_1	0.05	---	0.15	13
A_2	0.95	1.00	1.05	
D	7.00 BSC.			4
D_1	5.00 BSC.			7,8
E	7.00 BSC.			4
E_1	5.00 BSC.			7,8
L	0.45	0.60	0.75	
N	32			
e	0.50 BSC.			
b	0.17	0.22	0.27	9
b1	0.17	0.20	0.23	
ccc	---	---	0.08	
ddd	---	---	0.08	

SYMBOL	ALL DIMENSIONS IN MILLIMETERS			NOTE
	MIN.	NOM.	MAX.	
A	---	---	1.20	
A_1	0.05	---	0.15	13
A_2	0.95	1.00	1.05	
D	7.00 BSC.			4
D_1	5.00 BSC.			7,8
E	7.00 BSC.			4
E_1	5.00 BSC.			7,8
L	0.45	0.60	0.75	
N	40			
e	0.40 BSC.			
b	0.13	0.18	0.23	9
b1	0.13	0.16	0.19	
ccc	---	---	0.08	
ddd	---	---	0.08	

Amkor Technology, Inc.
Chandler, Arizona, USA
Anam Semiconductor, Inc.,
Seoul, Korea
Amkor Technology Philippines, Inc.
Manila, Philippines

Amkor Technology / ANAM Semiconductor

TITLE: PACKAGE OUTLINE, MATRIX, ePAD TQFP, 5 X 5 mm BODY, 1.00/0.10 mm FORM, 1.00 mm THICK (OPTIONAL ePAD)

SIZE: A3 | DWG NUMBER: 40579 | REV: 02

SCALE: 5:1 | PRINTING IS SCALED TO FIT DO NOT SCALE DRAWING | SHEET: 2 OF 2

THE DRAWINGS AND INFORMATION CONTAINED HEREIN ARE THE EXCLUSIVE PROPERTY OF AMKOR/ANAM. THE INFORMATION, DRAWINGS AND DESIGN CONCEPTS CONTAINED HEREIN ARE CONFIDENTIAL, PROPRIETARY, SHALL BE MAINTAINED IN STRICT CONFIDENCE AND SHALL NOT BE RELEASED TO ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AMKOR/ANAM.

AMKOR/ANAM CONFIDENTIAL

FORM NO. MDFORM2J.DWG