



Plastic Dual In-line Package (PDIP)

PDIP has a proven track record and is a common choice for assembly of logic, memory, microcontrollers and other devices for use in a wide range of applications. The straight leads with 100 mil pitch allow for easy board mounting (through-hole wave soldering) or socket insertion.

Features

- Standard JEDEC package outlines
- Multi-die production capability
- Turnkey test services, including strip test options
- Green materials are standard – Pb-free and RoHS compliant

Services and Support

Amkor has a broad base of resources available to help customers bring quality new products to market quickly and at the lowest possible cost.

- Full package characterization
- Thermal, mechanical stress and electrical performance modeling
- Turnkey assembly, test and drop ship
- World class reliability testing and failure analysis

PDIP

Reliability Qualification

Amkor package qualification uses three independent production lots and a minimum of 77 units per test group.

- Moisture Sensitivity Characterization JEDEC Level 1, 85°C/85% RH, 168 hours
- uHAST 130°C/85% RH, No bias, 96 hours
- Temp Cycle -65°C/+150°C, 500 cycles
- High Temp Storage 150°C, 1000 hours

Process Highlights

- Wafer backgrinding services available
- Multiple die and die stacking capability
- Matte Sn lead finish is standard
- Laser mark on package body
- Pcc wire bonding standard, Ag wire available

Test Services

- Program generation/conversion
- Wafer probe
- Burn-in capabilities
- -55°C to +165°C test available
- Strip test available

Shipping Options

- Clear anti-static tube, 20 inch
- Drop ship


Visit Amkor Technology online for locations and to view the most current product information.



D3971
Rev Date: 3/15

PDIP

Cross-section PDIP



Configuration Options

PDIP Nominal Package Dimensions (mils)

Lead Count	Shoulder Width	Body Width	Body Length	Body Thickness	Standoff	Lead Pitch	JEDEC
8	300	252	365	130	15	100	MS-001
14	300	252	750	130	15	100	MS-001
16	300	252	750	130	15	100	MS-001
18	300	252	900	130	15	100	MS-001
20	300	252	1030	130	15	100	MS-001
24	300	252	1250	130	15	100	MS-001
24	600	540	1250	150	15	100	MS-011
28	600	540	1450	150	15	100	MS-011
40	600	540	2060	150	15	100	MS-011

Visit Amkor Technology online for locations and to view the most current product information.



With respect to the information in this document, Amkor makes no guarantee or warranty of its accuracy or that the use of such information will not infringe upon the intellectual rights of third parties. Amkor shall not be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon it and no patent or other license is implied hereby. This document does not in any way extend or modify Amkor's warranty on any product beyond that set forth in its standard terms and conditions of sale. Amkor reserves the right to make changes in its product and specifications at any time and without notice. The Amkor name and logo are registered trademarks of Amkor Technology, Inc. All other trademarks mentioned are property of their respective companies. © 2015, Amkor Technology Incorporated. All Rights Reserved.

D3971
Rev Date: 3/15